


5000T

5 TON AIR-OPERATED DOUBLE TOGGLE HOT STAMPING PRESS



FEATURES

- Precision Machined 4" Wide Dovetailed Head Ram
- Dovetailed Die Holder
- Accurate Easy-to-Adjust Foil Advance
- Simple to Unload Foil Takeup
- Ground Steel Worktable with 3" Diameter Acme Screw Adjustment
- Head Speed Controls
- Heavy Duty Extra Rigid Frame
- Air Filter, Pressure Regulator & Automatic Lubricator

**5 TON
CAPACITY**

KF
KENSOL-FRANKLIN

HOT STAMPING MACHINES

KF5000T

5 TON AIR-OPERATED DOUBLE TOGGLE HOT STAMPING PRESS

SPECIFICATIONS

Max Opening Under Head:	9.50"
Hot Stamps Items up to:	6.50"
Overall Height:	38.25"
Net Weight:	700 lbs.
Head Stroke:	0-3" Standard
Throat Depth:	9.25"
Pressure Range:	0-5 Tons
Foil Advance:	Electric Motor
Heat Control:	Solid State Digital Indicating
Standard Head Sizes:	6" x 12" - 2000 Watts 6" x 8" - 1050 Watts 10" x 15" - 4000 Watts
Press Controls:	Programmable Logic-Based System with Operator Interface Panel
Actuation:	Simultaneous Lite-Touch Anti-Tie Down 2 Hand Buttons w/Pinch Point Interlock
Electrical Requirements:	6" x 8" 110V A.C. Larger sizes 220V, 1 Phase
Compressed Air Requirements:42 Cu. Ft. Free Air/Stroke @ 80 p.s.i.
Work Table:	Pre-Drilled Ground Steel

STANDARD VARIATIONS AVAILABLE

- Specialty Code Conformance: NEMA, JIC, etc.
- Larger Work Table
- Larger Platen Sizes
- Expanded Dwell Timer Range

AUTOMATION AVAILABLE

- Auto Cycle Slide Table
- Rotary Index Table
- Automatic Parts Loading Systems
- Automatic Parts Removal Systems
- Special Protective Enclosures
- "Light Curtain" Operator Protection



HOT STAMPING MACHINES

117 DEAN AVENUE, FRANKLIN, MA 02038
TELEPHONE (508) 528-2021 • FAX (508) 520-7129 • EMAIL: thomsgroup@meganet.net

Made in U.S.A.

Appropriate safety devices should always be used. KF Kensol-Franklin will quote or advise on protective equipment for your application upon request.

